



FIRE PROTECTION

AC918ME (M08400)

Electromagnetic FIRE DOOR HOLDERS

Reinforced aluminium housing - with release button

Floor mounting IP52

Door holders are generally linked to a fire system that will automatically release the doors in case of a fire by switching the power off. If required, it can also be manually operated by the release button.

STANDARD FEATURE

Mounted in a reinforced aluminium housing with a spring loaded device to eliminate residual magnetism, including a diode for protection, manual release button and electrical terminal connections.

This door holder is specially designed for use in areas of vandalism (schools, colleges, public area...) or industrial areas (warehouse, exhibition centre, supermarket, hospital...) or can be suited to every type of fire protection system.

Complete with fitting instructions and flat keeper plate.

TECHNICAL SPECIFICATIONS

Holding Force - **40Kg**

Voltage - **24VDC or 48VDC**

Nominal power at 20°C - **2W**

Protection Class - **III**

Protection Rating - **IP52 EN60529**

Electrical Connection - **Terminal Board**

Box Colour - **Grey RAL 9002 painted steel**

In Conformity with standards **NF S 61.937**
and **IN 1155**

| ITEM | Holding Force | Voltage | Diode |
|-----------|---------------|---------|-------|
| AC918ME07 | 40KG | 24VDC | YES |
| AC918ME08 | 40KG | 48VDC | YES |

